



PROBLEND™



equipment & tools

Reliable. Flexible. Ownable.

ProBlend's line of durable, reliable cleaning machinery is designed to meet the needs of your business today and tomorrow. Financing programs include purchase, lease or rent to own, with flexible, competitive terms. Your local ProBlend representative can help you determine the equipment and program that's right for you.

SPARKOZ

AUTONOMOUS CLEANING ROBOTS

“Never-Lost” 360° Navigation

Full coverage, zero missed spots

Adaptive Cleaning

Perfect results on different floors

Self-Charging & Auto-Draining

True hands off operation



THE FUTURE OF CLEANING,
AT YOUR SERVICE.

See the entire product line at ProBlendSolutions.com

Sparkoz - Autonomous Cleaning Robots



TN70-PRO - Disc Brush

Autonomous Floor Cleaning Robot. With its cutting-edge technology and unparalleled cleaning performance, the TN70 is the ultimate solution for all your cleaning needs. At the heart of its exceptional capabilities lies its unique 20" single giant brush, designed to consistently deliver immaculate results. 28 inch brush cleaning width for disc. 18.5 gallon solution tank capacity. 13.2 gallon recovery tank capacity. 100 Ah battery capacity. 21960 ft²/h cleaning efficiency.

- Precise movement and mapping, ensures thorough and efficient cleaning in various environments.
- Intelligent obstacle detection allows TN70 to navigate around obstacles seamlessly, minimizing disruptions and ensuring safe operation.
- User-friendly interface with intuitive controls for easy operation and seamless integration into any cleaning routine.

Available with Auto Charging or Auto Workstation.

Add ons include: Disinfection module, dust mop system and safety light.



TN70-PRO - Cylindrical Brush

Autonomous Floor Cleaning Robot. Redefining Industrial Floor Care Efficiency. The TN70 Pro CB combines high-performance sweeping and scrubbing in a single autonomous pass—eliminating the need for two separate machines. 24v 400w dual brush roller motor. 600 rpm brush rotating speed. 20.5 inch cylindrical brush cleaning width. 2 liter trash bin capacity. 21960 ft²/h cleaning efficiency.

Same charging and add ons as Disc Brush.



TN10-PRO w/Automatic Workstation

Autonomous Robot Floor Scrubber. TN10's compact and flexible design, powered by advanced AI navigation, allows it to navigate small and complex spaces effortlessly. Optimize your cleaning operations with a compact, lightweight, and affordable solution that offers powerful commercial cleaning at a fraction of the cost. Zero inch edge distance. 57 lbs gross weight. 23 inch accessible width. 8138 ft²/h cleaning efficiency.

- Detailed mapping technology enables systematic coverage and customized cleaning schedules.
- Automatic charging stations ensure multiple 100% autonomous cleaning missions per day.
- Quiet operation and compact design suitable for offices, retail, and commercial spaces.
- **Optional manual mode**, complete with a convenient telescoping handle offers flexibility to manually control the robot in complex or hard-to-reach areas, ensuring every inch of your space is thoroughly cleaned.



Dishmachines - Chemical Sanitizing Door Type



WAREFORCE® I-E

Internal Sump. Single rack, convertible for straight-through or corner application, 90-second cycle, 39 racks per hour, 1.02 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.



WAREFORCE® I-E-FL (Front Loading Machine) WAREFORCE® I-E-LTH (with booster heater)



WAREFORCE® I HH

Internal Sump. 27" tall chamber, single rack, convertible for straight-through or corner application, 90-second cycle, 39 racks per hour, 1.61 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.



WAREFORCE® II

Dual rack straight, 74 racks per hour, 1.17 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, three selectable wash cycles, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.



WAREFORCE® IIC

Same specifications as the WAREFORCE® II, except for corner installations. Please specify right front (R) or left front (L) door opening.



Dishmachines - High Temperature Sanitizing Door Type



WAREFORCE® HT-180

Single rack, field convertible for straight-through or corner application, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 0.89 gallons per rack, self-draining stainless steel wash pump assembly, universal timer, four selectable wash cycles, top mounted controls, exhaust vent fan control, front stainless steel dress panel.

Also available without booster heater or front loading.



WAREFORCE® HT-180 with Ventless & Energy Recovery

No vent hood required. Accommodates a wide range of water inlet temperatures and operates with only a cold water connection. Door interlock and pressure regulator included. Cleans 39 racks per hour. **Also available in front loading.**



WAREFORCE® HT-180 HH-E

27" tall chamber, single rack, field convertible for straight-through or corner application, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 1.36 gallons per rack, self-draining stainless steel wash pump assembly, dual counter-rotating lower wash arms, universal timer, four selectable wash cycles, top mounted controls, delimer switch, auto start/stop, exhaust vent fan control, front stainless steel dress panel.



WAREFORCE® HT-180HH-E with Ventless & Energy Recovery

See WAREFORCE® HT-180 VENTLESS specs above.
Cleans 37 racks per hour.



WAREFORCE® NXP-180

Single 57 second cycle, field convertible, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 0.89 gallons per rack, top mounted controls, delimer switch, exhaust vent fan control.



Dishmachines - Glasswashers



WAREFORCE® DG-E

Chemical sanitizing. Fill and dump with sustaining heater, 90-second cycle, 40 racks per hour, 1.16 gallons per rack, accommodates glasses and wares up to 11" high, functions as both a glasswasher and a dishwasher, easy access controls, electromechanical timer and two half-racks included.,



WAREFORCE® DG-HT-E-SEER-S

High temperature sanitizing. Recirculating, 20 racks per hour, 0.65 gallons per rack, Soft Start, built-in booster heater with Sani-Sure™ final rinse system, double wall construction, pumped drain, universal timer, digital LED control panel, three selectable cycles, one peg and one combination rack included.



WAREFORCE® CG

Chemical sanitizing. Rotary-type, cleans 1,200 glasses per hour, uses 10 gallons of water per hour, single switch operation, built-in chemical pumps and priming switches, hot or cold fresh water final rinse, convenient chemical storage and easy access scrap screens. Clockwise rotation.

WAREFORCE® CG-115

115 Volt version of WAREFORCE® CG.



Dishmachines - Conveyors



WAREFORCE® 44 CONVEYOR

44" single tank dual-rated conveyor dishmachine with electric tank heat, 225 racks/hour and 0.68 gallons/rack for high temp, 209 racks/hour and 0.78 gallons/rack for chemical sanitizing, Adjust-A-Peak™ conveyor speed, EnergyGuard™ system, 25" standard height clearance, table limit switch, automatic fill, manual/automatic switch, whisper-quiet stainless steel pump assembly, exhaust vent fan control.

WAREFORCE® 66 CONVEYOR

Same specifications as WAREFORCE® 44, plus 22" pre-wash section.

Dishmachines - Undercounters



WAREFORCE® UL30

Chemical sanitizing. Fill and dump with sustaining heater, 24 racks per hour, 1.2 gallons per rack, double-wall construction, stainless steel wash pump assembly, pumped drain, electromechanical timer, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto fill, auto stop, one peg and one combination rack included.



WAREFORCE® UH30-FND

High temperature sanitizing. Fill and dump, 24 racks per hour, 1.1 gallons per rack, built-in booster heater with Sani-Sure™ final rinse system, double-wall construction, stainless steel wash pump assembly, pumped drain, universal timer, delimer cycle, built-in chemical pumps and priming switches, auto fill, auto stop, one peg and one combination rack included.



PROBLEND™

BEYOND CLEAN.

ProBlendSolutions.com

— member of the PROBLEND™ NETWORK —