

OT SOL

heavy-duty solvent cleaner & demulsifier
trabajo pesado limpiador solvente y desemulsionante

GENERAL DESCRIPTION:

Specialized heavy duty solvent cleaner and demulsifier. OT SOL effectively cleans slop oil, heavy grease, asphaltene, bunker oil and paraffin solutions while effectively separating the water. Used by major oil treatment companies to reclaim oil for recycling into reusable materials.

APPLICATIONS:

- Concentrated
- Non-Corrosive
- Multi-functional
- Pleasant Citrus Fragrance
- Free Rinsing

TYPICAL PROPERTIES:

Appearance	Pale Yellow
Flash Point	145°F
Odor	Citrus
pH	N/A
Specific Gravity	0.810
Water Solubility	N/A

DIRECTIONS:

Preheat material to be cleaned to a minimum of 75°C (167°F) or 90°C (194°F) for bunker oil. While agitating, via mechanical or air, inject ~3000 ppm of OT SOL to start the cleaning process. More may be required depending on temperature and agitation. Allow to mix for 30 minutes at temperature. Stop agitation and allow gravity to separate waste in to layers for recycling. Water will go to the bottom and oil to the top. Decant water layer and reclaim oil for recycling.

PRECAUTIONS:

DANGER. Combustible liquid. May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.

HANDLING and STORAGE:

Avoid release to the environment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required (See Section 8 on the SDS). Store locked up. Store in a well-ventilated place. Keep cool. Keep out of reach of children. Dispose of contents/container to an approved waste disposal plant.

CONTAINS:

Distillates (petroleum), hydrotreated light (CAS# 64742-47-8).

D.O.T. Proper Shipping Name:

Not regulated for U.S. ground transport in non-bulk containers (<119 gallons).

PACKAGING:

55 Gallons

PRODUCT IDENTIFICATION:

Bulk Product
Number: 19221



NOTICE: Because conditions of use and laws and regulations may differ from one location to another and change with time, purchaser is responsible for determining if this product and the information in this document are appropriate for purchaser's application. Purchaser assumes all risk of appropriate handling and disposal. THIS PRODUCT IS SOLD WITHOUT WARRANTY; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

SOLVENT



PROBLEND[®]

INDUSTRIAL SERIES

ProBlendCommercial.com
Manufactured By: Seatex, Ltd. 445 TX Hwy 36 Rosenberg, TX 77471