

PROBLEND™



warewash
equipment

Professional Cleaning Solutions

ProBlendSolutions.com



Chemical Sanitizing Door-Type



WAREFORCE® I-E

Internal Sump. Single rack, convertible for straight-through or corner application, 90-second cycle, 39 racks per hour, 1.02 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.

WAREFORCE® I-E-FL **WAREFORCE I-E Front Loading Machine.**

WAREFORCE® I-E-LTH **WAREFORCE I-E with booster heater.**

WAREFORCE® I HH

Internal Sump. 27" tall chamber, single rack, convertible for straight-through or corner application, 90-second cycle, 39 racks per hour, 1.61 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.

WAREFORCE® II

Dual rack straight, 74 racks per hour, 1.17 gallons per rack, self-draining stainless steel wash pump assembly, air gap, electromechanical timer, three selectable wash cycles, top mounted controls, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto start/stop, built-in stainless steel scrap accumulator.

WAREFORCE® IIC

Same specifications as the WAREFORCE II, except for corner installations. Please specify right front (R) or left front (L) door opening.



Glasswashers



WAREFORCE® DG-E

Chemical sanitizing, fill and dump with sustaining heater, 90-second cycle, 40 racks per hour, 1.16 gallons per rack, accommodates glasses and wares up to 11" high, functions as both a glasswasher and a dishwasher, easy access controls, electromechanical timer and two half-racks included.



WAREFORCE® DG-E-SEER-S

High temperature sanitizing, recirculating, 20 racks per hour, 0.65 gallons per rack, Soft Start, built-in booster heater with Sani-Sure™ final rinse system, double wall construction, pumped drain, universal timer, digital LED control panel, three selectable cycles, one peg and one combination rack included.



WAREFORCE® CG

Chemical sanitizing, rotary-type, cleans 1,200 glasses per hour, uses 10 gallons of water per hour, single switch operation, built-in chemical pumps and priming switches, hot or cold fresh water final rinse, convenient chemical storage and easy access scrap screens. Clockwise rotation.

WAREFORCE® CG-115 **115 volt version of WAREFORCE CG.**



High Temperature Sanitizing Door-Type



WAREFORCE® HT-180

Single rack, field convertible for straight-through or corner application, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 0.89 gallons per rack, self-draining stainless steel wash pump assembly, universal timer, four selectable wash cycles, top mounted controls, delimer switch, auto start/stop, exhaust vent fan control, front stainless steel dress panel.

WAREFORCE® HT-180 without Booster Heater

WAREFORCE® HT-180 with Ventless & Energy Recovery

No vent hood required. Accommodates a wide range of water inlet temperatures and operates with only a cold water connection. Door interlock and pressure regulator included. Cleans 39 racks per hour.

WAREFORCE® HT-180HH-E

27" tall chamber, single rack, field convertible for straight-through or corner application, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 1.36 gallons per rack, self-draining stainless steel wash pump assembly, dual counter-rotating lower wash arms, universal timer, four selectable wash cycles, top mounted controls, delimer switch, auto start/stop, exhaust vent fan control, front stainless steel dress panel.

WAREFORCE® HT-180HH-E with Ventless & Energy Recovery

See WAREFORCE® HT-180 VENTLESS specs above. Cleans 37 racks per hour.

WAREFORCE® NXP-180

Single 57 second cycle, field convertible, electric tank heat, built-in booster heater with Sani-Sure™ final rinse system, 58 racks per hour, 0.89 gallons per rack, top mounted controls, delimer switch, exhaust vent fan control.



Conveyor



WAREFORCE® 44

44" single tank dual-rated conveyor dishmachine with electric tank heat, 225 racks/hour and 0.68 gallons/rack for high temp, 209 racks/hour and 0.78 gallons/rack for chemical sanitizing, Adjust-A-Peak™ conveyor speed, EnergyGuard™ system, 25" standard height clearance, table limit switch, automatic fill, manual/automatic switch, whisper-quiet stainless steel pump assembly, exhaust vent fan control.

WAREFORCE® 66

Same specifications as WAREFORCE® 44, plus 22" pre-wash section.

Undercounters



WAREFORCE® UL30

Chemical sanitizing, fill and dump with sustaining heater, 24 racks per hour, 1.2 gallons per rack, double-wall construction, stainless steel wash pump assembly, pumped drain, electromechanical timer, delimer switch, low product indicator light, built-in chemical pumps and priming switches, auto fill, auto stop, one peg and one combination rack included.

WAREFORCE® UH30-FND

High temperature sanitizing, fill and dump, 24 racks per hour, 1.1 gallons per rack, built-in booster heater with Sani-Sure™ final rinse system, double-wall construction, stainless steel wash pump assembly, pumped drain, universal timer, delimer cycle, built-in chemical pumps and priming switches, auto fill, auto stop, one peg and one combination rack included.



Dishmachine Accessories

Name	Type	Price
460 V Electrical	HT-180 Models Conveyors	
Back Panel	Undercounters	
Blower Dryer	Conveyors	
Casters (Set of 4)	Undercounters	
Cold Water Thermostat	Conveyors	
Drain Water Tempering Kit	DG-E-SEER-S & UH30-FND HT Door-Types Conveyors	
Dual Point Connection	Conveyors	
Booster Heater - 17.2 kW	Conveyors	
Booster Heater - 30 kW	Conveyors	
False Panel	I-E, I-X, HT-180 & NXP-180 I HH & HT-180HH-E	
Flanged Feet	Chem. & HT Door-Types Conveyors	
Front Dress Panel	I-E & I-HH	
Half Rack	DG-E	
Low Product Audible Alarm	Chem. Door-Types	
Machine Stand - 6 in.	Undercounters	
Machine Stand - 18 in.	Undercounters	
Pressure Regulator - 1/2 in.	Undercounters & Door Types Conveyors	
Pressure Regulator - 3/4 in.	I-E-LTH, I-E-FL, II & II-C	
Replacement Cartridge for SPS	Undercounters & Glass	
Scale Prevention System (SPS)	Undercounters & Glass	
Scrap Tray	CG & CG-115	
Side Enclosure Panels Kit	Glasswashers	
Side Loader 23 in. Hooded	Conveyors	
Side Loader 23 in. Unhooded	Conveyors	
Side Loader 30 in. Hooded	Conveyors	
Side Loader 30 in. Unhooded	Conveyors	
Single Phase	HT Door-Types	
Vent Cowl Collars	Conveyors	
Water Hammer Arrestor - 1/2 in.	All Types	
Water Hammer Arrestor - 3/4 in.	Chemical & HT VER Models	

Go-Boxes	Price
CG	
HT Door-Types Conveyors	
CG-115 & UL30	
Chem Door-Type & DG-E UH30-FND	

Dishtables	Price
Clean Side 24 in. - Left or Right Installation	
Clean Side 36 in. - Left or Right Installation	
Clean Side 48 in. - Left or Right Installation	
Clean Side 72 in. - Left or Right Installation	
Soiled Side 36 in. - Left or Right Installation	
Soiled Side 48 in. - Left or Right Installation	
Soiled Side 72 in. - Left or Right Installation	
Undercounter Table 48 in. - Left or Right	

Please call for Custom Dishtable Sizes & Specifications

Dishtable Accessories	Price
Overshelf 42 in.	
Overshelf 62 in.	
Pre-Rinse Basket with Slide Bar	
Pre-Rinse Spray for use with Overshelf	
Pre-Rinse Spray for use without Overshelf	
Undershelf 42 in.	

Dish Racks	Price
36 Compartment Rack (4-1/8 in. Tall)	
36 Compartment Rack (5-5/8 in. Tall)	
36 Compartment Rack (7 in. Tall)	
Combination Rack	
Peg Rack	
Sheet Pan Rack (HH & Conveyor models only)	

Water Treatment	Price
Scaltrol Water Treatment (SWT)	
Replacement Cartridge for SWT	